

WIDEX **CROS** MINI-BTE



STANDARD TECHNOLOGY

- True-Input technology
- WidexLink - Wireless connectivity
- Long battery life
- Volume control
- Multiple earware options

The WIDEX CROS mini-BTE uses our unique wireless WidexLink technology and the new TRUE ISP, True-Input technology platform. Volume control and program button (transmission on/off) are standard. Uses a size 312 battery.

COMPATIBILITY TABLE



	PASSION	FUSION	FASHION	9	<i>m</i> -CB	CIC	XP
DREAM440	x	x	x	x	x	x	x
DREAM330	x	x	x	x	x	x	x
DREAM220	x	x	x	x	x	x	x
DREAM110	x	x	x	x	x	x	x

WIDEX CROS COLOURS



KEY FEATURES

Volume control	X
Program button (transmission on/off)	X
Nano coating	X
Battery size	312
Water resistant	IP57
Colours	14

CROS-FA

PRODUCT DESCRIPTION:

Frequency range	Up to 10 kHz
Battery size	312
Working current	~ 1.2 mA
Battery life / hours (Type 312 Zn-Air, 145 mAh)	120 (>105)
Microphone mode	Locator/Omni
Program button (transmission on/off)	✓
Volume control	✓
Nano coating	✓*
Water resistant	IP57
Input range	113 dB SPL

* Microphone cover

RADIO SPECIFICATIONS

Frequency (range)	10.6 MHz (10.2-11.0 MHz)
RF bandwidth	660 kHz (-15 dB)
Channels	Single channel
Modulation	FSK
Radiated output power	29pW (-75dBm)
Magnetic field strength	-54 dbuV/m @ 10 m
Duty cycle	100 %
	Simplex
Conforms to the following standards/approvals	<ul style="list-style-type: none"> • EN/IEC 60950-1 • EN 300 330-2 • EN 301 489-1 • EN 301 489-3 • EN 62479 • FCC Part 15 C • FCC ID: TTY-DFA • CE Mark

OVERVIEW

